



**INSTALLATION INSTRUCTIONS FOR:  
LED DRIVER ENCLOSURE ONLY**  
(SEE FIXTURE INSTALLATION INSTRUCTIONS FOR  
FIXTURE SPECIFIC DETAILS & WIRING)

**WARNING: Risk of fire and electric shock! This fixture must be installed by a qualified electrician only! MAKE SURE ELECTRICAL CURRENT IS DISCONNECTED BEFORE MAKING ELECTRICAL SPLICES**

**DISCONNECT POWER**

1. UNWRAP ALL FIXTURE COMPONENTS INCLUDING SMALL PARTS BAGS ENCLOSED
2. SCREW {2} 2-1/2" 8-32 SCREWS TO THE UNIVERSAL MOUNTING BRACKET IN THE HOLES SPACED AT 3-1/2 INCHES APART AS SHOWN
3. SECURE UNIVERSAL MOUNTING BRACKET TO 4" J-BOX (BY OTHERS)
4. RAISE FIXTURE AND DRIVER ENCLOSURE CLOSE TO 4" J-BOX (BY OTHERS) AND PERFORM ELECTRICAL CONNECTIONS PER FIXTURE INSTALLATION INSTRUCTIONS
5. ALIGN FIXTURE CANOPY TO HOLES ON DRIVER ENCLOSURE AND SECURE BOTH THE FIXTURE CANOPY AND THE DRIVER ENCLOSURE TO THE {2} 2-1/2" 8-32 SCREWS USING THE 8-32 ACORN NUTS PROVIDED

**RECONNECT POWER**