

CIRCLE ACOUSTIC SILENCIO FAN PENDANT



MOUNTING

- Fixture comes with 10ft cord
- Mounts to 3 1/2"-4" J Box
- P5L versions comes with LED driver mounted in fixture canopy except L15 and 18 which requires surface canopy or remote enclosure chosen below
- Additional aircraft cable system with 120" adjustable cables for support

OPTICAL SYSTEM

- PS Interchangeable screw-in LED lamps (lamp not included)
- P5L- 64 degree reflector

- ELECTRICAL PS * 120V input
 - * 25W, 25VA (max 25W lamp LED) * Medium E26 base socket
 - P5L Integrated downlight LED

WARRANTY

ETL/UL Listed for US and Canada. Suitable for damp location

5 year full warranty

DIMMABLE

• PS - Dimmable with compatible lamp

• P5L - 0-10V dimming to 1%

VOLTAGE •120V Input (PS) •120~277V (P5L)

CONSTRUCTION

Fins made of ½" thick 65% PET Recycled fiber and 35% PET Virgin Fiber, 100% recyclable, environmentally safe. White linen shade/diffuser, silver metal support ring for sturdy construction, canopy and cord color of $% \left\{ \left(1\right) \right\} =\left\{ \left(1\right) \right\}$ your choice, selected below (contact factory for custom support ring finish)

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog # EXAMPLE CATALOG # SCF-12-CIR-30-S-PT-P5L3-30-8

SHADE Style	SHAPE/SIZE *SEE DRAWING ABOVE	CANOPY/CORE FINISH * SILVER SUPPORT RING		FIN FINISH		ELECTRICAL		COLOR TEMP * PSL LED ONLY		CRI * P5L LED ONLY	
□ SCF-12	□ CIR-30	□S	Silver	□PT	Pewter Gray	□ PS	25 watt medium base socket *lamp by others	□ 30	3000K	□ 8	80
	□ CIR-48	□В	Black	\square SL	Slate Gray	□ P5L3	3000lm 0-10v Dimming	□ 35	3000K	□ 9	90
		□W	White*	□WH	White	□ P5L6	6000lm 0-10v Dimming	□ 40	4000K		
			*available for PS only	□BU	Blue	□ P5L8	8000lm 0-10v Dimming				
				□ВК	Black	□ P5L12	12000lm 0-10v Dimming				
				□TN	Tan	□ P5L15	15000lm 0-10v Dimming				
				□С	Custom *consult factory	□ P5L18	18000lm 0-10v Dimming				