

TRIANGLE ACOUSTIC SILENCIO FAN PENDANT



MOUNTING

- Fixture comes with 10ft cord
- Mounts to 3 1/2" - 4" J Box
- P5L versions comes with LED driver mounted in fixture canopy except L15 and 18 which requires surface canopy or remote enclosure chosen below
- Additional aircraft cable system with 120" adjustable cables for support

OPTICAL SYSTEM

- PS - Interchangeable screw-in LED lamps (lamp not included)
- P5L - 64 degree reflector

ELECTRICAL

- PS - * 120V input
- * 25W, 25VA (max 25W lamp LED)
- * Medium E26 base socket
- P5L - Integrated downlight LED

LISTING

ETL/UL Listed for US and Canada. Suitable for damp location

WARRANTY

5 year full warranty

DIMMABLE

- PS - Dimmable with compatible lamp
- P5L - 0-10V dimming to 1%

VOLTAGE

- 120V Input (PS) • 120~277V (P5L)

CONSTRUCTION

Fins made of 1/2" thick 65% PET Recycled fiber and 35% PET Virgin Fiber, 100% recyclable, environmentally safe. White linen shade/diffuser, silver metal support ring for sturdy construction, canopy and cord color of your choice, selected below (contact factory for custom support ring finish)

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #
EXAMPLE CATALOG # SCF-12-TRI-36-S-PT-P5L3-30-8

SHADE STYLE	SHAPE/SIZE *SEE DRAWING ABOVE	CANOPY/CORE FINISH * SILVER SUPPORT RING	FIN FINISH	ELECTRICAL	COLOR TEMP * P5L LED ONLY	CRI * P5L LED ONLY
<input type="checkbox"/> SCF-12	<input type="checkbox"/> TRI-36 <input type="checkbox"/> TRI-48	<input type="checkbox"/> S Silver <input type="checkbox"/> B Black <input type="checkbox"/> W White* *available for PS only	<input type="checkbox"/> PT Pewter Gray <input type="checkbox"/> SL Slate Gray <input type="checkbox"/> WH White <input type="checkbox"/> BU Blue <input type="checkbox"/> BK Black <input type="checkbox"/> TN Tan <input type="checkbox"/> C Custom *consult factory	<input type="checkbox"/> PS 25 watt medium base socket *lamp by others <input type="checkbox"/> P5L3 3000lm 0-10v Dimming <input type="checkbox"/> P5L6 6000lm 0-10v Dimming <input type="checkbox"/> P5L8 8000lm 0-10v Dimming <input type="checkbox"/> P5L12 12000lm 0-10v Dimming <input type="checkbox"/> P5L15 15000lm 0-10v Dimming <input type="checkbox"/> P5L18 18000lm 0-10v Dimming	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3000K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 8 80 <input type="checkbox"/> 9 90