

ACOUSTIC SILENCIO SINGLE DRUM - SURFACE OR SUSPENDED



LED MODULE

- LED
- 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

CONSTRUCTION

- 18 GA steel chassis
- Acrylic diffuser with ½" thick PET Felt manufactured with 65% PET-Recycled Fiber and 35% PET Virgin Fiber, 100% recyclable, environmentally safe.

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

Cable (3 cable system, 50" adjustable), or
Stem Mounting (25" stem, 45 degree swivel), or
Surface Mounting
** Contact Factory for custom lengths

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #
EXAMPLE CATALOG # SCD-18-S-PT/SV4-40D18-30-9

SHADE STYLE	SHAPE **see drawings on next page	MATERIAL	ELECTRICAL	LUMEN OUTPUT	COLOR TEMP.	CRI
<input type="checkbox"/> SCD	<input type="checkbox"/> 18-S 18" SINGLE DRUM	<input type="checkbox"/> PT Pewter Gray <input type="checkbox"/> SL Slate Gray <input type="checkbox"/> WH White <input type="checkbox"/> BU Blue <input type="checkbox"/> BK Black <input type="checkbox"/> TN Tan <input type="checkbox"/> C Custom *consult factory	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A18 2000LM Triac Dimming <input type="checkbox"/> 40D18 4000LM 0-10V Dimming <input type="checkbox"/> 20D18 2000LM 0-10V Dimming	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90
<input type="checkbox"/> SCD	<input type="checkbox"/> 24-S 24" SINGLE DRUM <input type="checkbox"/> 36-S 36" SINGLE DRUM	<input type="checkbox"/> PT Pewter Gray <input type="checkbox"/> SL Slate Gray <input type="checkbox"/> WH White <input type="checkbox"/> BU Blue <input type="checkbox"/> BK Black <input type="checkbox"/> TN Tan <input type="checkbox"/> C Custom *consult factory	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A24 2000LM Triac Dimming <input type="checkbox"/> 40D24 4000LM 0-10V Dimming <input type="checkbox"/> 62D24 6000LM 0-10V Dimming	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90

MOUNTING	FINISH
<input type="checkbox"/> CCK-SV4 Aircraft Cable	<input type="checkbox"/> S Silver
<input type="checkbox"/> SCK-SV4 Stem Mount	<input type="checkbox"/> B Black
<input type="checkbox"/> (blank) Surface Mount	<input type="checkbox"/> W White
	<input type="checkbox"/> C Custom

ACOUSTIC SILENCIO DRUM - SURFACE OR SUSPENDED



LED MODULE

- LED
- 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

CONSTRUCTION

- 18 GA steel chassis
- **Single:** Acrylic diffuser with ½" thick PET Felt manufactured with 65% PET-Recycled Fiber and 35% PET Virgin Fiber, 100% recyclable, environmentally safe.
- **Double:** Inner drum: White acrylic with acrylic diffuser, outer drum ½" thick PET Felt manufactured with 65% PET-Recycled Fiber and 35% PET Virgin Fiber, 100% recyclable, environmentally safe.

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

Cable (3 cable system, 50" adjustable), or
Stem Mounting (25" stem, 45 degree swivel), or
Surface Mounting
** Contact Factory for custom lengths

ADDITIONAL SHADE DIMENSIONS

SHOWN AS SUSPENDED

