

# ACOUSTIC SILENCIO DOUBLE DRUM - SURFACE OR SUSPENDED



- LED MODULE**
- LED
  - 3000K, 3500K, 4000K
  - >90 CRI
  - 3500K noted below. Consult factory for performance of all CCTs
  - 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
  - 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
  - 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
  - 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

- CONSTRUCTION**
- 18 GA steel chassis
  - Inner drum: White acrylic with acrylic diffuser
  - Outer drum: 1/2" thick PET Felt manufactured with 65% PET-Recycled Fiber and 35% PET Virgin Fiber, 100% recyclable, environmentally safe.

**ELECTRICAL** 120-277V input power supply.

**LISTING** UL for US and Canada. Suitable for damp location.

**WARRANTY** 5 Year Full Warranty

**MOUNTING** Cable (3 cable system, 50" adjustable), or Stem Mounting (25" stem, 45 degree swivel), or Surface Mounting  
 \*\* Contact Factory for custom lengths

## BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #  
 EXAMPLE CATALOG # SCD-20-D-PT/SV4-40D18-30-9

SHADE STYLE	SHAPE <small>**see drawings on next page</small>	MATERIAL
<input type="checkbox"/> SCD	<input type="checkbox"/> 20-D 20" DOUBLE DRUM	<input type="checkbox"/> PT Pewter Gray <input type="checkbox"/> SL Slate Gray <input type="checkbox"/> WH White <input type="checkbox"/> BU Blue <input type="checkbox"/> BK Black <input type="checkbox"/> TN Tan <input type="checkbox"/> C Custom *consult factory
<input type="checkbox"/> SCD	<input type="checkbox"/> 28-D 28" DOUBLE DRUM <input type="checkbox"/> 36-D 36" DOUBLE DRUM	<input type="checkbox"/> PT Pewter Gray <input type="checkbox"/> SL Slate Gray <input type="checkbox"/> WH White <input type="checkbox"/> BU Blue <input type="checkbox"/> BK Black <input type="checkbox"/> TN Tan <input type="checkbox"/> C Custom *consult factory

ELECTRICAL	LUMEN OUTPUT	COLOR TEMP.	CRI
<input type="checkbox"/> SV4	<input type="checkbox"/> 34A18 2000LM Triac Dimming <input type="checkbox"/> 40D18 4000LM 0-10V Dimming <input type="checkbox"/> 20D18 2000LM 0-10V Dimming	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90
<input type="checkbox"/> SV4	<input type="checkbox"/> 34A24 2000LM Triac Dimming <input type="checkbox"/> 40D24 4000LM 0-10V Dimming <input type="checkbox"/> 62D24 6000LM 0-10V Dimming	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90

MOUNTING	FINISH
<input type="checkbox"/> CCK-SV4 Aircraft Cable	<input type="checkbox"/> S Silver
<input type="checkbox"/> SCK-SV4 Stem Mount	<input type="checkbox"/> B Black
<input type="checkbox"/> (blank) Surface Mount	<input type="checkbox"/> W White
	<input type="checkbox"/> C Custom

\*\*\* Specifications subject to change without notice.

**ACOUSTIC SILENCIO DOUBLE DRUM - SURFACE OR SUSPENDED**



- LED MODULE**
- LED
  - 3000K, 3500K, 4000K
  - >90 CRI
  - 3500K noted below. Consult factory for performance of all CCTs
  - 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
  - 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
  - 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
  - 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

- CONSTRUCTION**
- 18 GA steel chassis
  - Inner drum: White acrylic with acrylic diffuser
  - Outer drum: ½" thick PET Felt manufactured with 65% PET-Recycled Fiber and 35% PET Virgin Fiber, 100% recyclable, environmentally safe.

**ELECTRICAL** 120-277V input power supply.

**LISTING** UL for US and Canada. Suitable for damp location.

**WARRANTY** 5 Year Full Warranty

**MOUNTING** Cable (3 cable system, 50" adjustable), or Stem Mounting (25" stem, 45 degree swivel), or Surface Mounting  
\*\* Contact Factory for custom lengths

**ADDITIONAL SHADE DIMENSIONS**

SHOWN AS SUSPENDED

