

**ALUMINUM CYLINDER DOWNLIGHT PENDANT**



<b>LED MODULE</b>	Bridgelux diode with a 3 step MacAdams ellipse
<b>THERMAL MANAGEMENT</b>	The fixture is designed with a special passive heat sink to keep it running well below specifications. This ensures long life in excess of 50,000 hours.
<b>OPTICAL SYSTEM</b>	3.25" diameter aluminized reflectors are over 89% efficient and are interchangeable with a snap on connector.
<b>CONSTRUCTION</b>	Extruded aluminum heat sink, aluminum cylinder 20', 3 wire cord cuttable in the field
<b>ELECTRICAL</b>	The LED driver is mounted in fixture canopy
<b>LISTING</b>	UL for US and Canada, Suitable for listed damp location
<b>WARRANTY</b>	5 Year Full Warranty
<b>DIMMING</b>	Dimming capabilities to dim down to 1% 0-10V dimming
<b>VOLTAGE</b>	120~277V
<b>LUMEN OUTPUT</b>	Provides up to 12,000LM, 132.5 LPW Consult IES files for specific lumen values (available at <a href="http://www.chameleontg.com">www.chameleontg.com</a> )

**BUILD YOUR PRODUCT**

Grayed areas are codes for creating your lighting catalog #  
EXAMPLE CATALOG # **SP-CYL-W/P59-S-L6-30-8-R64**

STYLE	SHAPE	FINISH
<input type="checkbox"/> SP	<input type="checkbox"/> CYL Cylinder	<input type="checkbox"/> W White
		<input type="checkbox"/> B Black
		<input type="checkbox"/> S Silver

ELECTRICAL	CORD/CANOPY FINISH	LIGHT OUTPUT	COLOR TEMP.	CRI	BEAM SPREAD
<input type="checkbox"/> P59	<input type="checkbox"/> S Silver	<input type="checkbox"/> L3 3,000LM	<input type="checkbox"/> 30 3000	<input type="checkbox"/> 8 80	<input type="checkbox"/> R39 39 Degree
	<input type="checkbox"/> B Black	<input type="checkbox"/> L6 6,000LM	<input type="checkbox"/> 35 3500	<input type="checkbox"/> 9 90	<input type="checkbox"/> R64 64 Degree
		<input type="checkbox"/> L8 8,000LM	<input type="checkbox"/> 40 4000		
		<input type="checkbox"/> L12 12,000LM			

**OPTIONAL REMOTE EMERGENCY BACKUP (FIELD INSTALLED)**

<input type="checkbox"/> EM-ITA	Yes
<input type="checkbox"/> (blank)	No

\*\*\* Specifications subject to change without notice.