


## SPUN ALUMINUM INDUSTRIAL DOWNLIGHT PENDANT



**LED MODULE** Bridgelux diode with a 3 step MacAdams ellipse

**THERMAL MANAGEMENT** The fixture is designed with a special passive heat sink to keep it running well below specifications. This ensures long life in excess of 50,000 hours.

**OPTICAL SYSTEM** 3.25" diameter aluminized reflectors are over 89% efficient and are interchangeable with a snap on connector.

**CONSTRUCTION** Extruded aluminum heat sink, spun aluminum shade 20', 3 wire cord cuttable in the field

**ELECTRICAL** The LED driver is mounted in fixture canopy, except for models L15 and L18 which requires an included remote enclosure

**LISTING** UL for US and Canada, Suitable for listed damp location

**WARRANTY** 5 Year Full Warranty

**DIMMING** Dimming capabilities to dim down to 1% 0-10V dimming

**VOLTAGE** 120~277V

**LUMEN OUTPUT** Provides up to 18,000LM, 132.5 LPW  
Consult IES files for specific lumen values  
(available at [www.chameleontlg.com](http://www.chameleontlg.com))

## BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #

EXAMPLE CATALOG # SP-IN-S-O/P5-S-L3-30-8-R39

STYLE	SHAPE	FINISH	BOTTOM LENS
<input type="checkbox"/> SP	<input type="checkbox"/> IN Industrial	<input type="checkbox"/> W White <input type="checkbox"/> B Black <input type="checkbox"/> S Silver	<input type="checkbox"/> O Open

ELECTRICAL	CORD/CANOPY FINISH	LIGHT OUTPUT	COLOR TEMP.	CRI	BEAM SPREAD
<input type="checkbox"/> P5	<input type="checkbox"/> S Silver <input type="checkbox"/> B Black	<input type="checkbox"/> L3 3,000LM <input type="checkbox"/> L6 6,000LM <input type="checkbox"/> L8 8,000LM <input type="checkbox"/> L12 12,000LM <input type="checkbox"/> L15 15,000LM <input type="checkbox"/> L18 18,000LM	<input type="checkbox"/> 30 3000 <input type="checkbox"/> 35 3500 <input type="checkbox"/> 40 4000	<input type="checkbox"/> 8 80 <input type="checkbox"/> 9 90	<input type="checkbox"/> R39 39 Degree <input type="checkbox"/> R64 64 Degree

OPTIONAL UPLIGHT	CCT
<input type="checkbox"/> PUPL Yes <input type="checkbox"/> (blank) No	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K

\*2500LM, separate light engine with its own driver

\*field installed option to be installed with 2 wire cord supplied by contractor

### OPTIONAL REMOTE EMERGENCY BACKUP (FIELD INSTALLED)

<input type="checkbox"/> EM-ITA	Yes
<input type="checkbox"/> (blank)	No