

CLEANSE TRILAM SQUARE - SURFACE OR SUSPENDED



SHOWN AS SUSPENDED

**ADDITIONAL SHADE DIMENSIONS CAN BE FOUND ON THE NEXT PAGE

LED MODULE

- 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable 120V TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

SHADE

Cotton backed to styrene with clear vinyl coating (washable), closed white trilam diffuser

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

- Surface
 - Cable (3 cable system, 50" adjustable)
 - Stem Mounting (25" stem, 45 degree swivel)
- *** Contact Factory for custom pendant lengths

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #
EXAMPLE CATALOG # CSSV4-2020S-OT/SV4-34A18-30-9/CCK-SV4-S

SHADE STYLE	SIZE	MATERIAL				
<input type="checkbox"/> CSSV4	<input type="checkbox"/> 2020S	<input type="checkbox"/> OT	Orange Trilam	<input type="checkbox"/> GT	Green Trilam	
		<input type="checkbox"/> DGT	Slate Grey Trilam	<input type="checkbox"/> BLT	Black Trilam	
	<input type="checkbox"/> 2010S	<input type="checkbox"/> RT	Red Trilam	<input type="checkbox"/> WT	White Trilam	
		<input type="checkbox"/> CRT	Cream Trilam	<input type="checkbox"/> GTT	Green Tea Trilam	
	<input type="checkbox"/> CSSV4	<input type="checkbox"/> 2424S	<input type="checkbox"/> PT	Parsley Trilam	<input type="checkbox"/> CPT	Champagne Trilam
			<input type="checkbox"/> BT	Brown Trilam	<input type="checkbox"/> DFT	Daffodil Trilam
			<input type="checkbox"/> C	Custom		
			<input type="checkbox"/> OT	Orange Trilam	<input type="checkbox"/> GT	Green Trilam
<input type="checkbox"/> 2412S	<input type="checkbox"/> DGT	Slate Grey Trilam	<input type="checkbox"/> BLT	Black Trilam		
	<input type="checkbox"/> RT	Red Trilam	<input type="checkbox"/> WT	White Trilam		
<input type="checkbox"/> 3636S	<input type="checkbox"/> CRT	Cream Trilam	<input type="checkbox"/> GTT	Green Tea Trilam		
	<input type="checkbox"/> PT	Parsley Trilam	<input type="checkbox"/> CPT	Champagne Trilam		
<input type="checkbox"/> 3618S	<input type="checkbox"/> BT	Brown Trilam	<input type="checkbox"/> DFT	Daffodil Trilam		
	<input type="checkbox"/> C	Custom				

ELECTRICAL	LIGHT OUTPUT	COLOR TEMP.	CRI		
<input type="checkbox"/> SV4	<input type="checkbox"/> 34A18	<input type="checkbox"/> 30	3000K	<input type="checkbox"/> 9	90
		<input type="checkbox"/> 35	3500K		
	<input type="checkbox"/> 40	4000K			
<input type="checkbox"/> SV4	<input type="checkbox"/> 20D18	<input type="checkbox"/> 30	3000K	<input type="checkbox"/> 9	90
		<input type="checkbox"/> 35	3500K		
	<input type="checkbox"/> 40	4000K			
<input type="checkbox"/> SV4	<input type="checkbox"/> 40D18	<input type="checkbox"/> 30	3000K	<input type="checkbox"/> 9	90
		<input type="checkbox"/> 35	3500K		
	<input type="checkbox"/> 40	4000K			
<input type="checkbox"/> SV4	<input type="checkbox"/> 34A24	<input type="checkbox"/> 30	3000K	<input type="checkbox"/> 9	90
		<input type="checkbox"/> 35	3500K		
<input type="checkbox"/> SV4	<input type="checkbox"/> 40D24	<input type="checkbox"/> 40	4000K	<input type="checkbox"/> 9	90
		<input type="checkbox"/> 62D24	6000LM 0-10V Dimming		

MOUNTING	FINISH		
<input type="checkbox"/> CCK-SV4	Aircraft Cable	<input type="checkbox"/> S	Silver
<input type="checkbox"/> SCK-SV4	Stem Mount	<input type="checkbox"/> B	Black
<input type="checkbox"/> (blank)	Surface Mount	<input type="checkbox"/> W	White
		<input type="checkbox"/> C	Custom

CLEANSE TRILAM SQUARE - SURFACE OR SUSPENDED



SHOWN AS SUSPENDED

LED MODULE

- 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable 120V TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

SHADE Cotton backed to styrene with clear vinyl coating (washable), closed white trilam diffuser

CONSTRUCTION 18 GA steel chassis

ELECTRICAL 120-277V input power supply.

LISTING UL for US and Canada. Suitable for damp location.

WARRANTY 5 Year Full Warranty

MOUNTING

- Surface
 - Cable (3 cable system, 50" adjustable)
 - Stem Mounting (25" stem, 45 degree swivel)
- *** Contact Factory for custom pendant lengths

ADDITIONAL SHADE DIMENSIONS

DRAWINGS SHOWN AS SUSPENDED

