

CLEANSE TRILAM DRUM - SURFACE



**ADDITIONAL SHADE DIMENSIONS CAN BE FOUND ON THE NEXT PAGE

LED MODULE

- Samsung LED
- Static 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

Surface

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #
EXAMPLE CATALOG # CS-18X18R-S-L-SV4/SV4-34A18-30-9

STYLE	SHAPE	MATERIAL				LIGHT SOURCE	LIGHT SOURCE	WATTAGE	COLOR TEMP.	CRI				
<input type="checkbox"/> CS	<input type="checkbox"/> 18X18R <input type="checkbox"/> 18X9R	<input type="checkbox"/> OT	Orange Trilam	<input type="checkbox"/> LT	Iron Trilam	<input type="checkbox"/> SV4	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A18 34 Watt A Series LED	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90				
		<input type="checkbox"/> DGT	Slate Grey Trilam	<input type="checkbox"/> ST	Black Trilam									
	<input type="checkbox"/> TT	Tan Trilam	<input type="checkbox"/> WT	White Trilam										
	<input type="checkbox"/> RT	Red Trilam	<input type="checkbox"/> GTT	Green Tea Trilam	<input type="checkbox"/> 20D18 20 Watt D Series LED									
	<input type="checkbox"/> CRT	Cream Trilam	<input type="checkbox"/> CPT	Champagne Trilam										
	<input type="checkbox"/> PT	Parsley Trilam	<input type="checkbox"/> CNT	Canary Trilam										
	<input type="checkbox"/> BT	Brown Trilam	<input type="checkbox"/> DFT	Daffodil Trilam	<input type="checkbox"/> 40D18 40 Watt D Series LED									
	<input type="checkbox"/> GT	Green Trilam	<input type="checkbox"/> SNT	Snow Trilam										
	<input type="checkbox"/> MGT	Medium Grey Trilam												
	<input type="checkbox"/> CS	<input type="checkbox"/> 24X24R <input type="checkbox"/> 24X12R <input type="checkbox"/> 36X36R <input type="checkbox"/> 36X18R	<input type="checkbox"/> OT	Orange Trilam	<input type="checkbox"/> LT			Iron Trilam	<input type="checkbox"/> SV4		<input type="checkbox"/> SV4	<input type="checkbox"/> 34A24 34 Watt A Series LED	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90
			<input type="checkbox"/> DGT	Slate Grey Trilam	<input type="checkbox"/> ST			Black Trilam						
			<input type="checkbox"/> TT	Tan Trilam	<input type="checkbox"/> WT			White Trilam						
			<input type="checkbox"/> RT	Red Trilam	<input type="checkbox"/> GTT			Green Tea Trilam				<input type="checkbox"/> 40D24 40 Watt D Series LED		
<input type="checkbox"/> CRT		Cream Trilam	<input type="checkbox"/> CPT	Champagne Trilam										
<input type="checkbox"/> PT		Parsley Trilam	<input type="checkbox"/> CNT	Canary Trilam										
<input type="checkbox"/> BT		Brown Trilam	<input type="checkbox"/> DFT	Daffodil Trilam	<input type="checkbox"/> 62D24 62 Watt D Series LED									
<input type="checkbox"/> GT		Green Trilam	<input type="checkbox"/> SNT	Snow Trilam										
<input type="checkbox"/> MGT		Medium Grey Trilam												

OPTIONAL EMERGENCY BACKUP (FIELD INSTALLED)

- CHA-EM-ITA Yes
- (blank) No

CLEANSE TRILAM SQUARE - SURFACE



LED MODULE

- Samsung LED
- Static 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

CONSTRUCTION 18 GA steel chassis

ELECTRICAL 120-277V input power supply.

LISTING UL for US and Canada. Suitable for damp location.

WARRANTY 5 Year Full Warranty

MOUNTING Surface

ADDITIONAL SHADE DIMENSIONS

