

ACRYLIC INFUSED FABRIC SINGLE DRUM - SURFACE OR SUSPENDED



SHOWN AS SUSPENDED

LED MODULE

- 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable 120V TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

SHADE

- Outer drum fabric finish features 100% polyester fabric fused to acrylic. Washable with mild soap and water
- Diffuser created using UV stabilized, high transmission white acrylic

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

- Surface
 - Cable (3 cable system, 50" adjustable)
 - Stem Mounting (25" stem, 45 degree swivel)
- *** Contact Factory for custom pendant lengths

**ADDITIONAL SHADE DIMENSIONS CAN BE FOUND ON THE NEXT PAGE

BUILD YOUR PRODUCT

Grayed areas are codes for creating your lighting catalog #
 EXAMPLE CATALOG # FD-18-S-L/SV4-34A18-30-9/CCK-SV4-S

SHADE STYLE	SIZE	SHAPE	MATERIAL	ELECTRICAL	LIGHT OUTPUT	COLOR TEMP.	CRI
<input type="checkbox"/> FD	<input type="checkbox"/> 18	<input type="checkbox"/> S Single	<input type="checkbox"/> L White Linen <input type="checkbox"/> WA White Acrylic <input type="checkbox"/> O Oatmeal <input type="checkbox"/> HG Heathered Gray	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A18 2000LM Triac Dimming <input type="checkbox"/> 20D18 2000LM 0-10V Dimming <input type="checkbox"/> 40D18 4000LM 0-10V Dimming	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90
<input type="checkbox"/> FD	<input type="checkbox"/> 24 <input type="checkbox"/> 36	<input type="checkbox"/> S Single	<input type="checkbox"/> L White Linen <input type="checkbox"/> WA White Acrylic <input type="checkbox"/> O Oatmeal <input type="checkbox"/> HG Heathered Gray	<input type="checkbox"/> SV4	<input type="checkbox"/> 34A24 2000LM Triac Dimming <input type="checkbox"/> 40D24 4000LM 0-10V Dimming <input type="checkbox"/> 62D24 6000LM 0-10V Dimming	<input type="checkbox"/> 30 3000K <input type="checkbox"/> 35 3500K <input type="checkbox"/> 40 4000K	<input type="checkbox"/> 9 90

MOUNTING	FINISH
<input type="checkbox"/> CCK-SV4 Aircraft Cable	<input type="checkbox"/> S Silver
<input type="checkbox"/> SCK-SV4 Stem Mount	<input type="checkbox"/> B Black
<input type="checkbox"/> (blank) Surface Mount	<input type="checkbox"/> W White
	<input type="checkbox"/> C Custom

*** Specifications subject to change without notice.

ACRYLIC INFUSED FABRIC SINGLE DRUM - SURFACE OR SUSPENDED

LED MODULE

- 3000K, 3500K, 4000K
- >90 CRI
- 3500K noted below. Consult factory for performance of all CCTs
- 34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable 120V TRIAC to 10%
- 20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%
- 62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

SHADE

- Outer drum fabric finish features 100% polyester fabric fused to acrylic. Washable with mild soap and water
- Diffuser created using UV stabilized, high transmission white acrylic

CONSTRUCTION

18 GA steel chassis

ELECTRICAL

120-277V input power supply.

LISTING

UL for US and Canada. Suitable for damp location.

WARRANTY

5 Year Full Warranty

MOUNTING

- Surface
 - Cable (3 cable system, 50" adjustable)
 - Stem Mounting (25" stem, 45 degree swivel)
- *** Contact Factory for custom pendant lengths



SHOWN AS SUSPENDED

ADDITIONAL SHADE DIMENSIONS

DRAWINGS SHOWN AS SUSPENDED

