


TAPERED FABRIC CONE - SURFACE OR SUSPENDED



LED MODULE

- 3000K, 3500K, 4000K
- >90 CRI

• 3500K noted below. Consult factory for performance of all CCTs

34A - 34 Watt Nominal, min 2000 delivered lumens, 59 LPW, dimmable 120V TRIAC to 10%

20D - 24 Watt Nominal, min 2000 delivered lumens, 86 LPW, dimmable 0-10V to 1% 40D - 48 Watt Nominal, min 4000 delivered lumens, 86 LPW, dimmable 0-10V to 1%

62D - 75 Watt Nominal, min 6000 delivered lumens, 82 LPW, dimmable 0-10V to 1%

Poly cotton blend (Kona finishes 100% cotton) laminated to styrene, closed linda white diffuser

CONSTRUCTION 18 GA steel chassis

> ELECTRICAL 120-277V input power supply. LISTING $\ensuremath{\mathsf{UL}}$ for $\ensuremath{\mathsf{US}}$ and Canada. Suitable for damp location.

WARRANTY 5 Year Full Warranty

MOUNTING

• Surface

- Cable (3 cable system, 50" adjustable)
- Stem Mounting (25" stem, 45 degree swivel)

 *** Contact Factory for custom pendant lengths

BUILD YOUR PRODUCT

SHOWN AS SUSPENDED

Grayed areas are codes for creating your lighting catalog # EXAMPLE CATALOG # TPRSV4-24-LW/SV4-34A18-30-9/CCK-SV4-S

SHADE STYLE	SIZE	MATERIAL				
□TPRSV4	□ 24	□AS	Ash	□BS	Blue Stone	
		□LW	Linda White	□OD	Olive Drab	
		□LP	Linda Parchment	□NB	Natural Burlap	
		□СН	Cream Homespun	□ CW	Camelot Wheat	
		□KN	Kona Navy	□СТ	Camelot Tusah	
		□RR	Roja Red	□МВ	Mystic Black	
				□С	Custom	

ELECTRICAL	LIGHT OUTPUT		COLOR TEMP.		CRI	
□SV4	□34A18	2000LM	□30	3000K	□9	90
		Triac Dimming	□35	3500K		
	□20D18	2000LM 0-10V Dimming	□ 40	4000K		
	□40D18	4000LM 0-10V Dimming				

MC	DUNTING	FINISH		
□ CCK-SV4	Aircraft Cable	□S	Silver	
□ SCK-SV4	Stem Mount	□В	Black	
□ (blank)	Surface Mount	□W	White	
		□С	Custom	